

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 August 2006 (17.08.2006)

PCT

(10) International Publication Number
WO 2006/085344 A1


- (51) International Patent Classification:
A43B 7/28 (2006.01) A43B 17/18 (2006.01)
- (21) International Application Number:
PCT/IT2005/000071
- (22) International Filing Date:
14 February 2005 (14.02.2005)
- (25) Filing Language: Italian
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): **FILA LUXEMBOURG S.A.R.L.** [LU/LU]; Boulevard Royal 26, L-2449 Luxembourg (LU).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **PISCIONERI, Conrad** [IT/IT]; 12 Via dei Soster, I-31044 Montebelluna (IT). **DE MARCHI, Roberto** [IT/IT]; 260 Via Schiavonesca Nuova, I-31040 Volpago Del Montello (IT).
- (74) Agents: **RIPAMONTI, Enrico** et al.; Ing. A. Giambro-
cono & C. S.R.L., 19/b Via Rosolino Pilo, I-20129 Milano
(IT).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report
— with amended claims

[Continued on next page]

(54) Title: SHOE HAVING AN INNER ADAPTABLE SURFACE ON WHICH THE WEARER'S FOOT RESTS



(57) Abstract: A shoe (1) of walking or sports type, comprising a sole (2) and a vamp (3) connected to said sole (2) and receiving the user's foot, this latter resting on a resting surface inside the shoe, said surface being preferably defined by the upper surface of an innersole (4) which lies inside the shoe (1) on the sole (3), in this latter there being provided a first container containing a first material defining one phase of a two-phase synthetic resin foam product, a second material defining the second phase of this product being contained in a second container (9), the second container (9) being frangible when subjected to pressure, so releasing the second material contained in it; the first container (8) of the first material contains the second container (9), this latter being surrounded by said first container (8) such that the second material released by said second container (9) enters the first material present in the first container (8), the mixing of these materials resulting in the curing of the resin foam product, at least part of said curing taking place with the user's foot resting on the resting surface, so shaping this latter to match the plantar region of said foot.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

SHOE HAVING AN INNER ADAPTABLE SURFACE ON WHICH THE WEARER'S FOOT RESTS

The present invention relates to a shoe, of walking or sports type, in
5 accordance with the introduction to the main claim.

A shoe is known to comprise a sole, generally constructed of an elastomer material, for example rubber or EVA, with which a vamp is associated to receive a user's foot. The user's plantar region rests on a resting surface of the sole; an innersole, the top of which contacts the foot, is preferably
10 disposed between the sole and the user's foot, to define said resting surface.

Shoes are known in which the resting surface for the user's foot can be shaped to mirror the user's plantar region. Generally, this shape is permanently assumed when the user uses the shoe for the first time.

15 The resting surface for the user's foot is usually shaped to mirror the plantar region thereof by using methods comprising the provision in the sole of a plurality of containers, a first container containing a first material of a two-phase synthetic resin foam product and at least a second container containing a second material of this product. On forming the
20 sole, these containers are positioned well separate from each other; however when the second container, made of a frangible material, is subjected to a suitable pressure, the second material of said product contained therein mixes with the first material present in the first container; this mixing results in a chemical reaction by which the two originally liquid
25 materials define a substance which solidifies within a short time. This resin foam substance (or product) inserted into the first container (the only

container remaining within the sole) enables this latter to assume a shape corresponding to the user's plantar region when the container is inserted into the shoe during the curing period of the foam substance. In this manner the foot resting surface within the shoe assumes the specific
5 shape of the plantar region of the user wearing it.

A first example of such a shoe is described in DE3114944 and describes a shoe having an innersole provided with a flexible envelope containing a plastic resin, in particular a polyurethane foam (or products deriving from polyfunctional isocyanates with polyalcohols) or a silicone rubber (for
10 example of SIR type). A number of containers of a hardening agent and, preferably, of a hardening accelerator are dispersed within this envelope, said agent being chosen such that on mixing with the plastic resin present in the first container it causes this resin to more or less rapidly cure. This curing results in an innersole having the consistency of an elastomer and
15 shaped as the foot of the user wearing the shoe during this process. The plurality of second containers are ruptured by subjecting the sole to a suitable pressure or by heat before inserting the innersole into the shoe; in any event, the curing time for the plastic resin is such that it terminates after the user has put the shoe on.

20 Although the aforesaid prior patent enables an innersole to be obtained shaped as the user's plantar region, it has the drawback that this shape is difficult to obtain because of the dispersion of the various containers containing the hardening agent within the container containing the plastic resin. To achieve a suitable distribution of the hardening agent within the
25 plastic resin, all the containers of this agent must be ruptured such as to cause this agent to disperse uniformly within said resin. As the containers

of this agent are numerous and are dispersed within the resin container, they may rupture incompletely so that part of said resin, not reached by any hardening agent, remains yieldable even after the innersole has been inserted into the shoe. Consequently the resting surface of the user's foot
5 does not become completely shaped as the user's plantar region and moreover, by presenting yieldable portions, does not offer adequate user comfort during use of the shoe.

DE2926246 describes a shoe presenting a sole, a vamp and an innersole containing silicone material in plastic form (unactivated material). The
10 innersole is shaped substantially as a container for this silicone material and presents an aperture through which a drying or hardening agent can be inserted which, on mixing with the silicone resin, causes it to harden or cure (in other words, it activates the resin). The hardening material is inserted into the innersole by a syringe.

15 After injecting this material, the innersole is suitably manipulated and inserted into the shoe above the sole. During the time in which the silicone material remains active, the shoe is worn by the user so that hardening of this material terminates under the pressure of the user's foot, this pressure shaping the foot in accordance with the plantar region.

20 This prior patent uses a syringe for inserting the hardening material into the innersole, a solution which is hardly practical. Moreover as a syringe is used, one of these substances may emerge through the point in which the syringe has been inserted into the innersole, at least during the commencement of mixing between the silicone material and the hardening
25 agent while manipulating the innersole.

US3985853 describes a further solution relative to an innersole shapeable

according to user's plantar region.

US3736673, which is the document of the state of the art considered the closest to the present invention, describes a shoe provided with an innersole able to assume generally the shape of a user's plantar region. A
5 second innersole is provided removably interconnected to and at least partly disposed below the first innersole, this second innersole having generally a U-shape and extending from that part of said first innersole normally positioned between the metatarsal region of said foot and the shoe heel region. Below the second innersole there is provided a U-
10 shaped bag element fixed to said second innersole, said element presenting a pair of parallel arms, symmetrically disposed about an interconnection portion. Within these arms there are disposed frangible containers, each containing a material defining a phase of a two-phase rigid foam product. The two materials are manually mixed by rupturing the
15 relative containers before inserting the second innersole into the shoe. Mixing takes place within the bag element and results in the creation, within the interconnection portion, of foam which rises into the U-shaped bag element and fills it completely. After this insertion the shoe is worn so that the pressure of the overlying foot results in expansion of the foamed
20 system and its hardening, to assume the shape of the plantar region.

This US patent presents various drawbacks including the fact that when the innersole is inserted into the shoe it is no longer separable from this latter. Moreover, because of the position of the containers of the two materials defining the foam product, rupturing the containers may not lead
25 to compete mixing of these materials within the transverse portion of the U-shaped element, with consequent incomplete foam creation within it.

Consequently, the U-shaped element is unable to correctly assume the shape of the user's plantar region so that the final shoe does not attain the objects of the patent, i.e. the shoe does not present an innersole shaped as the user's foot. Indeed, the possible incomplete mixing of the two materials of the foam product, resulting from the arrangement of the relative containers at the opposing arms of the U-shaped element, can result in the creation of parts of different rigidity within the element below the user's foot. These parts, if thick, can also cause pain to the user wearing the shoe; if the user is a child, an incorrect resting surface for the foot inside the shoe on a surface on which the child walks can cause microtraumas within the child's foot structure and within the lower limbs in general, microtraumas which could also lead to subsequent walking problems for the child.

In addition, as the second innersole presents a U-shaped element which can assume the shape of the user's foot, the innersole may not be able to completely copy the shape of that plantar region between the metatarsal region and the heel. In this respect, because of the U-shape of the deformable element, if there is any incorrect mixing of the two materials of the foam system, the innersole could yield at the region between the U-shaped arms of said element, with consequent lack of adequate support for the overlying foot portion. Again in this case the aforesaid problems related to the incomplete mixing of said materials could therefore appear.

The solution of this prior patent is also difficult to implement because of the need to create, within the arms of a U-shaped bag element, separate containers for the two materials of the foam product.

An object of the present invention is to provide an improved shoe in which

the resting surface for the foot of the user wearing it can be effectively shaped as the plantar region.

A particular object of the invention is to provide a shoe which is of simple construction and can be obtained at a lower cost than equivalent known shoes.

Another object of the invention is to provide a shoe which, even after various uses, is able to offer a new resting surface adapted to the user's foot if the previous resting surface has lost the previously given shape.

These and further objects which will be apparent to the expert of the art are attained by a shoe in accordance with the accompanying claims.

The present invention will be more apparent from the accompanying drawings, which are provided by way of non-limiting example and in which: Figure 1 is an exploded perspective view of a shoe according to the invention;

Figure 2 is a perspective view of part of a variant of the shoe according to the invention;

Figure 3 is a section on the line 3-3 of Figure 1;

Figure 4 is a section similar to that of Figure 3, but of another variant of the invention; and

Figure 5 is a section on the line 5-5 of Figure 4.

With reference to said figures, the invention provides a shoe indicated overall by 1 in Figure 1. It comprises a sole 2 on which a vamp 3 is disposed to define the seat for the foot of the user wearing the shoe. With a lower face 2A of the sole there are associated usual studs 4 formed by injection moulding onto the sole. Said sole face 2A, which contacts the ground, can evidently be of different shape while remaining within the

scope of the present invention.

When inside the shoe the user's foot lies on a resting surface preferably defined by the upper side 4 of an innersole 5 lying on an upper face 2B of the sole 2.

- 5 With the sole 2 there is associated a first container 8 in which a first material is disposed defining one phase of a two-phase synthetic resin foam product, a second material defining the second phase of this product being contained in a second container 9. This second container 9 is frangible under pressure to enable said materials to be mixed together and
10 allow the creation, by chemical action, of the resin foam product within the container 8.

According to the invention, the first container 8 contains the second container 9 which together define an insert 10 located inside the sole 2. In this manner, the second material of the foam product present in the
15 second container 9 can adequately mix with the first material of this product contained in the first container when this second container 9 ruptures. As the second container 9 is present within the first container 8, the emergence of the second material from said second container enables this material to reach every point of the first container and mix with the first
20 material present therein. By this means, the resin foam product exists at every point of the container 8.

More specifically, the first material contained in the first container 8 is a silicone resin for example of the type described in DE314944, or a silicone which vulcanizes at ambient temperature of the type described, for
25 example, in US3985853. A further example of the first material of the aforesaid resin foam product is that of a two-component silicone currently

produced by Rhodia Silicone, of which this material forms the first component.

The first material is contained in the first container 8 formed in known manner, for example of polyurethane (advantageously transparent), of
5 thickness between 200 and 400 microns. In any event, the container 8 has a thickness such as to withstand a pressure of at least 100 kg/cm^2 without rupturing.

The second material of the resin foam product is a suitable known hardening agent, possibly associated with a suitable accelerator, usable
10 with the first material to achieve solidification after its mixing with this latter. An example of this second material can be found in DE3114944.

This second material is contained in the second container 9, also made of plastic or polymer material, for example polyethylene, but having a smaller thickness than the first container 8. For example, the thickness of the
15 second container can be between 40 and 50 microns. In any event, the thickness of the container 8 is such that it can be ruptured or opened by acting on it with a stress or pressure at most equal to 5 kg/cm^2 and preferably $2\text{-}3 \text{ kg/cm}^2$.

To enable the second material to reach every point of the first container
20 after the second container 9 has been ruptured, this second container has an elongate shape and is disposed along the longitudinal axis W of the insert 10. Advantageously, said second container has a branched structure presenting a plurality of arms or branches 13 extending from a trunk 14, said trunk being disposed along the axis W and the branches 13
25 projecting from it towards the edges of the first container 8.

As stated, the second container 9 is contained in the first. Preferably, as

shown in Figure 3, this container is completely embedded within the first container 8 with the material present in this latter completely wrapping the second container 9 on all sides. Alternatively, the second container 9 can be in the form of a bag insertable into the first container 8 and presenting
5 opposing sidepieces 9A, 9B brought together and bonded perpendicular to a plane containing the insert 10, said sidepieces being hence perpendicular to a free face 8A of the container 8 (see Figure 5).

According to another characteristic of the invention, the insert 10 is positioned in a seat 11 provided in an intersole 17 present between the
10 innersole 4 and the sole 2. The seat 11 has the shape of the insert 10 and completely contains it. The intersole 17 is made of any elastomer material and is also to be considered part of the sole 2, even if it is preferably and advantageously removable from the interior of the vamp 3.

However the intersole 17 can also be made of a material other than an
15 elastomer, for example a natural material such as cork.

As an alternative, the seat 11 can be formed directly within the sole 2, as visible in Figure 2. Again in this case the seat 11 receives the insert 10 and has the shape essentially of the first container 8 which adapts to the interior of said seat 11.

20 By virtue of the present invention, a shoe is obtained having a resting surface for the foot contained in it which can be adapted to assume the shape of its plantar region. It will now be assumed that the invention is to be used to obtain this adapted resting surface. To achieve this, pressure is generated on the second container 9 or rather in correspondence with
25 different portions of this container, in order to rupture it and enable the contained material to emerge therefrom. As a result of this emergence

said material becomes distributed randomly about said container 9; by applying suitable manipulation this material becomes suitably distributed within the first container to reach every point thereof and to mix and interact with the first material contained therein. This operation must be
5 carried out within a predetermined time limit which is a function of the type of materials defining the resin foam system used; for example, this time may be two minutes, within which time the second material becomes distributed within the first container 8.

After this manipulation, the insert 10 is positioned in the seat 11 inside the
10 shoe; the innersole 4 is placed on it to cover it completely. When the shoe is worn, the user's weight produces the final shape of the resin foam product present in the insert 10, which hence assumes the shape of the user's plantar region.

It should be noted that the insert 10 lies in the seat 11 provided in the sole
15 2 such as to occupy a space corresponding to that part of the plantar region between the foot metatarsal region and the heel.

The invention is simple to implement and gives certain results. This is due to the aforescribed arrangement of the containers 8 and 9. In addition, as the insert 10 is removable from the shoe, it can be replaced by a new
20 insert (still to be shaped) whenever it becomes damaged with time, or with continued use of the shoe it no longer correctly matches the user's plantar region.

Different embodiments of the invention have been described, however others can be obtained (for example by suitably choosing the material of
25 the resin foam product to be used or the shape of the single container 9 placed in the single container 8) while remaining within the scope of the

invention as defined in the accompanying claims.

CLAIMS

1. A shoe (1) of walking or sports type, comprising a sole (2) and a vamp (3) connected to said sole (2) and receiving the user's foot, this latter resting on a resting surface inside the shoe, said surface being
5 preferably defined by the upper surface of an innersole (4) which lies inside the shoe (1) on the sole (2), in this latter there being provided a first container (8) containing a first material defining one phase of a two-phase synthetic resin foam product, a second material defining the second phase of this product being contained in a second container (9), the second
10 container (9) being frangible when subjected to pressure, so releasing the second material contained in it, characterised in that the first container (8) of the first material contains the second container (9), this latter being surrounded by said first container (8) such that the second material released by said container (9) enters the first material present in the first
15 container (8), the mixing of these materials resulting in the curing of the resin foam product, at least part of said curing taking place with the user's foot resting on the resting surface, so shaping this latter to match the plantar region of said foot.
2. A shoe as claimed in claim 1, characterised in that the first
20 container (8) and the second container (9) inserted into it define an insert (10) to be positioned in a seat (11) in the sole (2).
3. A shoe as claimed in claim 2, characterised in that the seat (11) occupies a part of the sole corresponding to that region of the user's foot lying between the metatarsal region and the heel thereof.
- 25 4. A shoe as claimed in claim 2, characterised in that the seat (11) is provided in a intersole (17) to be disposed below the innersole inside the

shoe, on a part (2) of the sole which contacts the ground.

5. A shoe as claimed in claim 2, characterised in that the seat (11) is provided in that part of the sole (2) which contacts the ground.

6. A shoe as claimed in claim 1, characterised in that the second
5 container (9) is disposed along the longitudinal axis (W) of the first container (8).

7. A shoe as claimed in claim 6, characterised in that the second container (9) is shaped substantially as a tree presenting a trunk (14) disposed along the longitudinal axis (W) of the first container and arms or
10 branches (13) projecting from said trunk towards the edge of said second container.

8. A shoe as claimed in claim 1, characterised in that the first container is made of polymer material.

9. A shoe as claimed in claim 8, characterised in that said container
15 withstands pressure stresses at least equal to or greater than 100 kg/cm^2 .

10. A shoe as claimed in claim 1, characterised in that the second container (9) is of polymer material.

11. A shoe as claimed in claim 10, characterised in that the second container (9) ruptures at pressures at least equal to or greater than 2-3
20 kg/cm^2 .

12. A shoe as claimed in claim 1, characterised in that the material contained in the first container (8) completely wraps the second container (9).

13. A shoe as claimed in claim 1, characterised in that the second
25 container (9) is defined by a bag presenting sidepieces (9A, 9B) joined together and disposed perpendicular to a face (8A) of the first container

parallel to the plane in which this latter lies.

AMENDED CLAIMS

[received by the International Bureau on 22nd May 2006 (22.05.06);
original claim 1 has been amended; original claim 7 has been deleted;
remaining claims have been renumbered accordingly]

1. A shoe (1) of walking or sports type, comprising a sole (2) and a
vamp (3) connected to said sole (2) and receiving the user's foot, this
latter resting on a resting surface inside the shoe, said surface being
5 preferably defined by the upper surface of an innersole (4) which lies
inside the shoe (1) on the sole (2), in this latter there being provided a first
container (8) containing a first material defining one phase of a two-phase
synthetic resin foam product, a second material defining the second phase
of this product being contained in a second container (9), the second
10 container (9) being frangible when subjected to pressure, so releasing the
second material contained in it, the first container (8) of the first material
containing the second container (9), this latter being surrounded by said
first container (8) such that the second material released by said container
(9) enters the first material present in the first container (8), the mixing of
15 these materials resulting in the curing of the resin foam product, at least
part of said curing taking place with the user's foot resting on the resting
surface, so shaping this latter to match the plantar region of said foot,
characterised in that the second container (9) is shaped substantially as a
tree presenting a trunk (14) disposed along the longitudinal axis (W) of the
20 first container and arms or branches (13) projecting from said trunk
towards the edge of said second container.
2. A shoe as claimed in claim 1, characterised in that the first
container (8) and the second container (9) inserted into it define an insert
(10) to be positioned in a seat (11) in the sole (2).
- 25 3. A shoe as claimed in claim 2, characterised in that the seat (11)
occupies a part of the sole corresponding to that region of the user's foot

lying between the metatarsal region and the heel thereof.

4. A shoe as claimed in claim 2, characterised in that the seat (11) is provided in a intersole (17) to be disposed below the innersole inside the shoe, on a part (2) of the sole which contacts the ground.

5 5. A shoe as claimed in claim 2, characterised in that the seat (11) is provided in that part of the sole (2) which contacts the ground.

6. A shoe as claimed in claim 1, characterised in that the second container (9) is disposed along the longitudinal axis (W) of the first container (8).

10 7. A shoe as claimed in claim 1, characterised in that the first container is made of polymer material.


8. A shoe as claimed in claim 7, characterised in that said container withstands pressure stresses at least equal to or greater than 100 kg/cm^2 .




9. A shoe as claimed in claim 1, characterised in that the second
15 container (9) is of polymer material.

10. A shoe as claimed in claim 9, characterised in that the second container (9) ruptures at pressures at least equal to or greater than $2\text{-}3 \text{ kg/cm}^2$.

11. A shoe as claimed in claim 1, characterised in that the material
20 contained in the first container (8) completely wraps the second container (9).

12. A shoe as claimed in claim 1, characterised in that the second container (9) is defined by a bag presenting sidepieces (9A, 9B) joined together and disposed perpendicular to a face (8A) of the first container
25 parallel to the plane in which this latter lies.





INTERNATIONAL SEARCH REPORT

International Application No
PCT/IT2005/000071A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A43B7/28 A43B17/18

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A43B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 098 315 A (HOFFMANN, III ET AL) 8 August 2000 (2000-08-08) column 2, line 30 - column 3, line 3	1-6,8-12
A	US 4 742 625 A (SYDOR ET AL) 10 May 1988 (1988-05-10) the whole document	4,5



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

15 September 2005

Date of mailing of the international search report

22/09/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Claudel, B

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IT2005/000071

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 6098315	A	08-08-2000	AU WO	5874696 A 9638063 A1	18-12-1996 05-12-1996
US 4742625	A	10-05-1988	CA	1240506 A1	16-08-1988